DALI DISPLAY 7" DT8

Commissioning tool and light control unit for two DALI circuits

- Commissioning tool for up to 2 DALI circuits:
  - Configuration of up to 16 groups, up to 16 scenes (brightness and/or CCT or RGB), daytime sequences and stored sequences
  - Creation of weekly plans/assignment of sequences to week days
- Light control unit for up to two DALI circuits:
  - Calling up to 16 scenes
  - Calling daytime sequences, stored sequences and weekly plans
  - One fixed daytime sequence is stored by default
- The DALI Display can be programmed with customised screens including desired features on request
- If the DALI Display is used in combination with the DALI touchpanel, then daytime sequences or sequences stored in the display can be called via the touch panel

Dimensions

Length	200 mm
Width	20 mm
Height	150 mm

DALI CE IP20 RoHS

TECHNICAL DATA

Electric supply	36 V, included in the scope of delivery
Interfaces	2 x DALI, 1 x USB, 1 x Ethernet
Output signal	DALI (two DALI circuits possible)
DALI Standard	IEC 62386 (incl. Device Type 8)
Display screen	7" touch screen with 24 Bit colour depth
Background lighting	RGB LEDs
Screens	Customised screens with desired programmable features
Software updates	via Ethernet or USB
Protection class	IP 20

ORDER DATA

Art.No.	Control device
LTP-1029	DALI Dislpay DT8

Notes
* For DALI bus supply, one pc. K-DALI-PS or one pc. K-DALI-PS2 must be used in addition.