

DALI TOUCHPANEL

Control device for DALI luminaires

- Wall operating panel for DALI luminaires with colour control according to DALI Standard Device Type 8
- Brightness, colour temperature and RGB colour control
- Calling mood lights (precondition: luminaires have stored light moods)
- In combination with DALI Display 7" or with the DALI CDC or DALI Sequencer module, daytime sequences or sequences stored in the display can be called via the touch panel
- Broadcast control (all luminaires) or group-wise control (up to two groups; luminaires must be grouped in advance)
- The control buttons on the DALI Touchpanel can be equipped with other functions/features on request and the labelling fields can be adjusted accordingly
- Multiple touch panels per DALI circuit can be used as well

TECHNICAL DATA

Electric supply	via DALI-Bus
Current consumption	4 mA
Input/output signal	DALI
DALI Standard	IEC 62386 (incl. Device Type 8)
Identification plate	Standard identification plate as shown in the figure
Features	Customisable features, programmable as defined
Protection class	by user IP 20
Temperature	0°C–50°C
Housing material	ABS

DALI



Dimensions

Length 82 mm
Height 111 mm

Colours | Designs

White
RAL 9010

DALI  IP20 

ORDER DATA

Art.No.	Control device
LTP-1028	DALI Touchpanel DT8