

# K-ZWALLY

## NeoLink wall control panel for NeoLink/ZigBee luminaires



- Luminaires can be switched on and off (power switch is recommended)
- Brightness can be adjusted steplessly (5–100 % for colour temperatures and CIE-xy colours)
- Colour temperature can be adjusted steplessly, from 1,800 K up to 16,000 K with transition to red range
- Stepless RGB sequence
- For luminaires with direct and indirect light portion, each light portion can be controlled separately from the other – both in brightness mode and colour mode.
- Automatic daytime sequence (standard sequence or seasonal sequence)
- Installing a NeoLink network (automatic registration of NeoLink luminaires in the network)
- Resetting an installed NeoLink network (automatic deregistration of NeoLink luminaires from the network)
- Integration in a higher-ranking NeoLink network (starting from a NeoLink Box or a NeoLink USB Stick) is possible
- Flush mounted in conventional wall sockets with a minimum depth of 61 mm



## TECHNICAL DATA

Operation	Endless control potentiometer with push button
Operating voltage	100 V – 240 VAC
Frequency range	50/60 Hz
Power consumption	0.3 W
Housing colour	Black
Connection / Installation	platinum terminal / flush-mounted in wall socket in accordance with DIN 49073 with a minimum depth of 61 mm
Pin diameter	4 mm (compatible with popular switch programs* – contries on request); including adapter sleeve for 6 mm shaft diameter
Tests / approvals	CE / RoHs Conformity
Other	Installation and operating instructions are included at the time of delivery; the cover frame is not included (optional accessory)

## ORDER DATA

Art.No.	NeoLink Wheel Control
K-ZWALLY-11	NeoLink Wheel Control, standard course of daylight, UTC
K-ZWALLY-21	NeoLink Wheel Control, seasonal course of daylight, UTC
K-ZWALLY-31	NeoLink Wheel Control, standard course of daylight, UTC+1
K-ZWALLY-41	NeoLink Wheel Control, seasonal course of daylight, UTC+1
Art.No.	Accessory
K-Z1000051	Central plate with rotary knob, JUNG AS500 series, A1540 WW, alpine white 
K-Z1000050	Frame one-fold, JUNG AS500 series, AS581 WW, alpine white 
K-Z1000052	Frame two-fold, JUNG AS500 series, AS582 WW, alpine white 